



MARK	DATE	REVISION	REVISER	APP .BY
1				
2				
3				

MODEL NO			S50L			
MATERIAL			HOUSING-ABS			
			LENS-AS			
			REFLECTOR-HEAT RESISTING ABS			
COLOR OF LENS			RED(    ), AMBER(    ), GREEN(    ), BLUE(    )			
FLASHES PER MIN.			60 ~ 80			
USE VOLT.	LED	CURRENT	DC12V	0.08W	Max.0.050A	
			DC24V			
			AC110V		0.045A	
			AC220V		0.045A	
PROTECTION GRADE			WATER & DUST PROOF IP44			
CABLE ENTRY			ø9 LEAD HOLE			
COLOR OF HOUSING			MAKER STANDARD			
ACTION			LED STEADY/FLASHING LIGHT			

ISO2768-1 : CLASS OF TOLERANCE						SURFACE FINISH		-	-	-	-	1	-
FOR LINEAR DIMENSIONS		f	m	(C)	v			Nr.	DWG. NO.	TITLE/ NAME	MAT'L	QTY	REFERENCE
	0.5~3	±0.05	±0.1	±0.2	-			DSND BY	CHKD BY	CHKD BY	APRV BY	VIEW	DATE
	3~6			±0.3	±0.5			S.H.KIM	J.H.PARK		J.K.HAN	3	2019.03.20
	6~30	±0.1	±0.2	±0.5	±1			TITLE S50L OUTLINE DRAWING					
	30~120	±0.15	±0.3	±0.8	±1.5			MODEL S50L					
	120~400	±0.2	±0.5	±1.2	±2.5			DWG. NO. S50L_OUT					
FOR ANGULAR DIMENSIONS	0~10	±1°	±1°30'	±3°				SCALE N/S SIZE A4 REV 00 SHEET 1/1					
	10~50	±0°30'	±1°	±2°									
	50~120	±0°20'	±0°30'	±1°									
	120~400	±0°10'	±0°13'	±0°30'									

**Qlight**

A4(297X210)