



MARK	DATE	REVISION	REVISER	APP .BY
①				
②				
③				

MODEL NO		SBE150		
MATERIAL		HOUSING-AL		
		BELL HOUSING-AL		
USE VOLT.	CURRENT	DC24V	MAX. 0.044A	
		AC110V	MAX. 0.044A	
		AC220V	MAX. 0.022A	
VOLUME		MAX. 95dB at 1m		
PROTECTION GRADE		WATER & DUST PROOF IP56		
CABLE ENTRY		1/2" NPT		
COLOR OF HOUSING		MUNSELL NO. 7.5BG 7/2		
ACTION		INTERNAL PEASURE ALARM BELL		

ISO2768-1 : CLASS OF TOLERANCE						SURFACE FINISH	-	-	-	-	1	-		
FOR LINEAR DIMENSIONS		f	m	Ⓒ	v		Nr.	DWG. NO.	TITLE/ NAME		MAT'L	QT'Y	REFERENCE	
	0.5~3	±0.05	±0.1	±0.2	-				DSND BY	CHKD BY	CHKD BY	APRV BY	VIEW	DATE
	3~6			±0.3	±0.5				S.H.KIM	J.H.PARK		J.K.HAN	3	2016.08.30
	6~30	±0.1	±0.2	±0.5	±1				TITLE SBE150 OUTLINE DRAWING			MODEL SBE150		
	30~120	±0.15	±0.3	±0.8	±1.5									
	120~400	±0.2	±0.5	±1.2	±2.5									
400~1000	±0.3	±0.8	±2	±4						DWG. NO. SBE150_OUT				
FOR ANGULAR DIMENSIONS	0~10	±1°		±1°30'	±3°									
	10~50	±0°30'		±1°	±2°									
	50~120	±0°20'		±0°30'	±1°									
	120~400	±0°10'		±0°13'	±0°30'									
							SCALE N/S		SIZE A4	REV 00	SHEET 1/1			

A4(297X210)