



MARK	DATE	REVISION	REVISER	APP. BY
1				
2				
3				

MODEL NO			SSL100M			
MATERIAL			HOUSING-AL			
			LENS-PC			
COLOR OF LENS			RED			
USE VOLT.	LED	CURRENT	DC24V	0.08W	0.151A	
			AC110V		0.040A	
			AC220V		0.040A	
PROTECTION GRADE			WATER & DUST PROOF IP68			
CONNECTOR			M12-5PIN or C10 CABLE			
COLOR OF HOUSING			MAKER STANDARD			
ACTION			LED STEADY			

ISO2768-1 : CLASS OF TOLERANCE						SURFACE FINISH	-	-	-	-	1	-	
FOR LINEAR DIMENSIONS		f	m	Ⓒ	v		Nr.	DWG. NO.	TITLE/ NAME	MAT'L	QTY	REFERENCE	
	0.5~3	±0.05	±0.1	±0.2	-		DSND BY	CHKD BY	CHKD BY	APRV BY	VIEW	DATE	
	3~6			±0.3	±0.5		C.S.GWAK	J.H.PARK		J.K.HAN	3	2021.08.30	
	6~30	±0.1	±0.2	±0.5	±1								
	30~120	±0.15	±0.3	±0.8	±1.5								
	120~400	±0.2	±0.5	±1.2	±2.5								
FOR ANGULAR DIMENSIONS	400~1000	±0.3	±0.8	±2	±4		TITLE			MODEL			
							SSL100M OUTLINE DRAWING			SSL100M			
										DWG. NO.			
										SSL100M_OUT			
										SCALE	SIZE	REV	SHEET
										1/1	A4	01	1/1