



LAYER	L
1	368
2	398
3	428
4	458
5	488

MARK	DATE	REVISION	REVISER	APP .BY
1				
2				
3				

MODEL NO			STA25SLM			
MATERIAL			HOUSING-AL			
			LENS-AS			
			-			
COLOR OF LENS			RED(), AMBER(), GREEN(), BLUE(), WHITE()			
USE VOLT.	LED	CURRENT	DC12V	0.08W	MAX. 0.080A	LAYER1
			DC24V		MAX. 0.040A	LAYER1
			AC110V		MAX. 0.020A	LAYER1
			AC220V		MAX. 0.020A	LAYER1
PROTECTION GRADE			WATER & DUST PROOF IP44			
COLOR OF HOUSING			MAKER STANDARD			
ACTION			LED STEADY LIGHT			

ISO2768-1 : CLASS OF TOLERANCE						SURFACE FINISH		-	-	-	-	1	-
FOR LINEAR DIMENSIONS		f	m	(C)	v			Nr.	DWG. NO.	TITLE/ NAME	MAT'L	QTY	REFERENCE
	0.5~3	±0.05	±0.1	±0.2	-			DSND BY	CHKD BY	CHKD BY	APRV BY	VIEW	DATE
	3~6			±0.3	±0.5			S.H.KIM	J.H.PARK		J.K.HAN	3	2016.08.30
	6~30	±0.1	±0.2	±0.5	±1			TITLE STA25SLM OUTLINE DRAWING					
	30~120	±0.15	±0.3	±0.8	±1.5			MODEL STA25SLM					
	120~400	±0.2	±0.5	±1.2	±2.5			DWG. NO. STA25SLM_OUT					
FOR ANGULAR DIMENSIONS	400~1000	±0.3	±0.8	±2	±4			SCALE N/S					
	0~10	±1°		±1°30'	±3°			SIZE A4					
	10~50	±0°30'		±1°	±2°			REV 00					
	50~120	±0°20'		±0°30'	±1°			SHEET 1/1					
	120~400	±0°10'		±0°13'	±0°30'								

