



| | | | | | | |
|--------------------|-----|---------|-------------------------|-----|-------------|--|
| MODEL NO | | | SAOL1 | | | |
| MATERIAL | | | HOUSING-PC | | | |
| | | | LENS-PC | | | |
| | | | POLE-SUS304 | | | |
| LIGHT SOURCE | | | LOW INTENSITY A TYPE | | | |
| LIGHT COLOR | | | RED | | | |
| USE VOLT. | LED | CURRENT | DC12V | 20W | MAX. 0.000A | |
| | | | DC24V | | MAX. 0.265A | |
| | | | AC110V | | MAX. 0.000A | |
| | | | AC220V | | | |
| LUMINOUS INTENSITY | | | 17cd ±25% | | | |
| PROTECTION GRADE | | | WATER & DUST PROOF IP56 | | | |
| CABLE ENTRY | | | ø20 CABLE ENTRY | | | |
| COLOR OF HOUSING | | | MAKER STANDARD | | | |
| ACTION | | | LED STEADY LIGHT | | | |

| ISO2768-1 : CLASS OF TOLERANCE | | | | | | SURFACE FINISH | - | - | - | - | 1 | - | |
|--------------------------------|---------|--------|------|--------|-----------|---|----------|---|-------------|------|------------|------|-----------|
| FOR LINEAR DIMENSIONS | | f | m | Ⓒ | v | | Nr. | DWG. NO. | TITLE/ NAME | | MAT'L | QT'Y | REFERENCE |
| | 0.5~3 | ±0.05 | ±0.1 | ±0.2 | - | DSND BY | CHKD BY | CHKD BY | APRV BY | VIEW | DATE | | |
| | 3~6 | | | ±0.3 | ±0.5 | S.H.KIM | J.H.PARK |  | J.K.HAN | 3 | 2019.03.20 | | |
| | 6~30 | ±0.1 | ±0.2 | ±0.5 | ±1 | TITLE | | | MODEL | | | | |
| | 30~120 | ±0.15 | ±0.3 | ±0.8 | ±1.5 | SAOL1 OUTLINE DRAWING | | | SAOL1 | | | | |
| | 120~400 | ±0.2 | ±0.5 | ±1.2 | ±2.5 |  | | | DWG. NO. | | | | |
| 400~1000 | ±0.3 | ±0.8 | ±2 | ±4 | SAOL1_OUT | | | | | | | | |
| FOR ANGULAR DIMENSIONS | 0~10 | ±1° | | ±1°30' | ±3° | | | | SCALE | | SIZE | REV | SHEET |
| | 10~50 | ±0°30' | | ±1° | ±2° | | | | N/S | | A4 | 00 | 1/1 |
| | 50~120 | ±0°20' | | ±0°30' | ±1° | | | | | | | | |
| | 120~400 | ±0°10' | | ±0°13' | ±0°30' | | | | | | | | |

A4(297X210)