




LAYER	L
1	153
2	194
3	235
4	278
5	317



MARK	DATE	REVISION	REVISER	APP.BY
△				
△				
△				

MODEL NO			STB45ML-Ex			
MATERIAL			HOUSING-PC			
			LENS-PC			
			UNDER BODY-AL			
COLOR OF LENS			RED(),AMBER(),GREEN(),BLUE(),WHITE()			
USE VOLT.	LED	CURRENT	AC/DC12V	0.08W	0.040A	LAYER1
			AC/DC24V		0.043A	LAYER1
VOLUME		MAX. 83dB at 1m				
PROTECTION GRADE		WATER & DUST PROOF IP54				
COLOR OF HOUSING		MAKER STANDARD				
ACTION		LED STEADY LIGHT				

ISO2768-1 : CLASS OF TOLERANCE						SURFACE FINISH	-	-	-	-	1	-
FOR LINEAR DIMENSIONS		f	m	⌀	v		Nr.	DWG. NO.	TITLE/ NAME	MAT'L	QTY	REFERENCE
	0.5~3	±0.05	±0.1	±0.2	-	DSND BY S.H.KIM	CHKD BY J.H.PARK	CHKD BY 	APRV BY J.K.HAN	VIEW 3	DATE 2019.03.20	
	3~6			±0.3	±0.5							
	6~30	±0.1	±0.2	±0.5	±1	TITLE STB45ML-Ex OUTLINE DRAWING		MODEL STB45ML-Ex				
	30~120	±0.15	±0.3	±0.8	±1.5				DWG. NO. STB45ML-Ex_OUT			
	120~400	±0.2	±0.5	±1.2	±2.5					SCALE N/S	SIZE A4	REV 01
400~1000	±0.3	±0.8	±2	±4								
FOR ANGULAR DIMENSIONS	0~10	±1°		±1°30'	±3°							
	10~50	±0°30'		±1°	±2°							
	50~120	±0°20'		±0°30'	±1°							
	120~400	±0°10'		±0°13'	±0°30'							