

LAYER	L
1	458
2	498
3	538
4	578
5	618

RJ45 LAN CONNECTOR

POWER CABLE


M18x1.5
THREAD

MARK	DATE	REVISION	REVISER	APP.BY
△				
△				
△				

MODEL NO	ST45L-ETN		
MATERIAL	HOUSING-ABS		
	LENS-AS		
	POL-AL		
COLOR OF LENS	RED(), AMBER(), GREEN(), BLUE()		
KIND OF SOUND	BZ	5 BUZZ SOUNDS	
	WS	5 WAGNING SOUNDS	
	WM	5 MAELODIES	
	WA	5 ALARMS	
VOLUME	MAX. 90dB at 1m		
PROTECTION GRADE	WATER & DUST PROOF IP23		
CABLE ENTRY	φ8 LEAD HOLE		
COLOR OF HOUSING	MAKER STANDARD		
ACTION	USB LED TOWER LAMP		

ISO2768-1 : CLASS OF TOLERANCE					
FOR LINEAR DIMENSIONS		f	m	Ⓢ	v
	0.5~3			±0.2	-
	3~6	±0.05	±0.1	±0.3	±0.5
	6~30	±0.1	±0.2	±0.5	±1
	30~120	±0.15	±0.3	±0.8	±1.5
	120~400	±0.2	±0.5	±1.2	±2.5
FOR ANGULAR DIMENSIONS	400~1000	±0.3	±0.8	±2	±4
	0~10	±1°		±1°30'	±3°
	10~50	±0°30'		±1°	±2°
	50~120	±0°20'		±0°30'	±1°
	120~400	±0°10'		±0°13'	±0°30'

SURFACE
FINISH

-	-	-	-	1	-
Nr.	DWG. NO.	TITLE/ NAME		MAT'L	REFERENCE
DSND BY	CHKD BY	CHKD BY	APRV BY	VIEW	DATE
S.H.KIM	J.H.PARK		J.K.HAN	3	2016.08.30
TITLE			MODEL		
ST45L-ETN OUTLINE DRAWING			ST45L-ETN		
			DWG. NO.		
			ST45L-ETN_OUT		
SCALE		SIZE	REV	SHEET	
N/S		A4	00	1/1	

A4(297X210)