



MARK	DATE	REVISION	REVISER	APP.BY
1				
2				
3				

MODEL NO			S150RS			
MATERIAL			HOUSING-SUS			
			LENS-PC			
			REFLECTOR-HEAT RESISTING ABS			
COLOR OF LENS			RED(), AMBER(), GREEN(), BLUE()			
FLASHES PER MIN.			60 ~ 80			
USE VOLT.	XENON	CURRENT	DC12V	6W	MAX. 1.001A	
			DC24V		MAX. 0.616A	
			AC110V		MAX. 0.133A	
			AC220V		MAX. 0.106A	
PROTECTION GRADE			WATER & DUST PROOF IP44			
CABLE ENTRY			φ10 LEAD HOLE			
COLOR OF HOUSING			MAKER STANDARD			
ACTION			XENON LAMP STROBE LIGHT			

ISO2768-1 : CLASS OF TOLERANCE						SURFACE FINISH	-	-	-	-	1	-				
FOR LINEAR DIMENSIONS		f	m	Ⓒ	v		Nr.	DWG. NO.		TITLE/ NAME		MAT'L	QTY	REFERENCE		
	0.5~3	±0.05	±0.1	±0.2	-	DSND BY S.H.KIM	CHKD BY J.H.PARK		APRV BY J.K.HAN	VIEW 3	DATE 2016.08.30					
	3~6			±0.3	±0.5											
	6~30	±0.1	±0.2	±0.5	±1											
	30~120	±0.15	±0.3	±0.8	±1.5											
	120~400	±0.2	±0.5	±1.2	±2.5											
400~1000	±0.3	±0.8	±2	±4												
FOR ANGULAR DIMENSIONS	0~10	±1°		±1°30'	±3°				TITLE S150RS OUTLINE DRAWING		MODEL S150RS					
	10~50	±0°30'		±1°	±2°						DWG. NO. S150RS_OUT					
	50~120	±0°20'		±0°30'	±1°						SCALE N/S			SIZE A4	REV 00	SHEET 1/1
	120~400	±0°10'		±0°13'	±0°30'											

Qlight

A4(297X210)