



MARK	DATE	REVISION	REVISER	APP.BY
1				
2				
3				

MODEL NO			S150RLR-FT			
MATERIAL			HOUSING-SUS			
			LENS-PC			
			REFLECTOR-HEAT RESISTING ABS			
COLOR OF LENS			RED(), AMBER(), GREEN(), BLUE()			
REV. PER MIN.			120 ~ 140			
USE VOLT.	POWER LED	CURRENT	DC12V	3W	MAX. 0.422A	
			DC24V		MAX. 0.266A	
			AC110V		MAX. 0.082A	
			AC220V		MAX. 0.041A	
PROTECTION GRADE			WATER & DUST PROOF IP44			
CABLE ENTRY			φ10 LEAD HOLE			
COLOR OF HOUSING			MAKER STANDARD			
ACTION			POWER LED REVOLVING WARNING LIGHT			

ISO2768-1 : CLASS OF TOLERANCE						SURFACE FINISH		-		-		-		1	-
FOR LINEAR DIMENSIONS		f	m	Ⓢ	v			Nr.	DWG. NO.	TITLE/ NAME		MAT'L	QTY	REFERENCE	
	0.5~3			±0.2	-			DSND BY	CHKD BY	CHKD BY		APRV BY	VIEW	DATE	
	3~6	±0.05	±0.1	±0.3	±0.5			S.H.KIM	J.H.PARK			J.K.HAN	3	2016.08.30	
	6~30	±0.1	±0.2	±0.5	±1			TITLE		S150RLR-FT		MODEL		S150RLR-FT	
	30~120	±0.15	±0.3	±0.8	±1.5			OUTLINE DRAWING							
	120~400	±0.2	±0.5	±1.2	±2.5			Qlight				DWG. NO.		S150RLR-FT_OUT	
FOR ANGULAR DIMENSIONS	400~1000	±0.3	±0.8	±2	±4							SCALE		N/S	
	0~10	±1°		±1°30'	±3°							SIZE		A4	
	10~50	±0°30'		±1°	±2°							REV		00	
	50~120	±0°20'		±0°30'	±1°							SHEET		1/1	
	120~400	±0°10'		±0°13'	±0°30'										