


MARK	DATE	REVISION	REVISER	APP .BY
1				
2				
3				

MODEL NO			S150RS-FT			
MATERIAL			HOUSING-SUS			
			LENS-PC			
			REFLECTOR-HEAT RESISTING ABS			
COLOR OF LENS			RED(), AMBER(), GREEN(), BLUE()			
FLASHES PER MIN.			60 ~ 80			
USE VOLT.	XENON	CURRENT	DC12V	6W	MAX. 1.001A	
			DC24V		MAX. 0.616A	
			AC110V		MAX. 0.133A	
			AC220V		MAX. 0.106A	
PROTECTION GRADE			WATER & DUST PROOF IP44			
CABLE ENTRY			φ10 LEAD HOLE			
COLOR OF HOUSING			MAKER STANDARD			
ACTION			XENON LAMP STROBE LIGHT			

ISO2768-1 : CLASS OF TOLERANCE						SURFACE FINISH		-	-	-	-	1	-
FOR LINEAR DIMENSIONS		f	m	(C)	v			Nr.	DWG. NO.	TITLE/ NAME	MAT'L	QTY	REFERENCE
	0.5~3	±0.05	±0.1	±0.2	-			DSND BY	CHKD BY	CHKD BY	APRV BY	VIEW	DATE
	3~6			±0.3	±0.5			S.H.KIM	J.H.PARK		J.K.HAN	3	2016.08.30
	6~30	±0.1	±0.2	±0.5	±1			TITLE S150RS-FT OUTLINE DRAWING					
	30~120	±0.15	±0.3	±0.8	±1.5			MODEL S150RS-FT					
	120~400	±0.2	±0.5	±1.2	±2.5			DWG. NO. S150RS-FT_OUT					
FOR ANGULAR DIMENSIONS	0~10		±1°	±1°30'	±3°			SCALE N/S SIZE A4 REV 00 SHEET 1/1					
	10~50		±0°30'	±1°	±2°								
	50~120		±0°20'	±0°30'	±1°								
	120~400		±0°10'	±0°13'	±0°30'								

A4(297X210)