



*POWER CABLE : DC TYPE - UL2464 AWG22(0.3sq X 2C) 450mm
AC TYPE - VCTFK (0.75sq) x 2C 450mm

MARK	DATE	REVISION	REVISER	APP. BY
△1				
△2				
△3				

MODEL NO		QGL/QGLC			
MATERIAL		SIDE COVER-ABS			
		LENS-PC			
		HEAT SINK-AL			
		BRACKET-SUS201			
MODEL		QGL-200/ QGLC-200	QGL-300/ QGLC-300	QGL-400/ QGLC-400	QGL-500/ QGLC-500
POWER CONSUMPTION	DC24V	3W	5W	7.5W	10.5W
	AC220V	-	7W	10W	12W
LED		CHIP LED			
PROTECTION GRADE		NON WATER-PROOF			

MODEL	A	B	C
QGL/ QGLC -200	200	177	16~130
QGL/ QGLC -300	300	277	16~230
QGL/ QGLC -400	400	377	16~330
QGL/ QGLC -500	500	477	16~430

ISO2768-1 : CLASS OF TOLERANCE						SURFACE FINISH		-	-	-	-	1	-
FOR LINEAR DIMENSIONS	0.5~3	±0.05	±0.1	±0.2	±0.3	±0.5		Nr.	DWG. NO.	TITLE/ NAME	MAT'L	QTY	REFERENCE
	3~6	±0.05	±0.1	±0.2	±0.3	±0.5		DSND BY	CHKD BY	CHKD BY	APRV BY	VIEW	DATE
	6~30	±0.1	±0.2	±0.5	±0.8	±1.5		C.S.GWAK	J.H.PARK		J.K.HAN	3	2021.07.27
	30~120	±0.15	±0.3	±0.8	±1.5	±2.5		TITLE QGL/QGLC OUTLINE DRAWING				MODEL QGL/QGLC	
	120~400	±0.2	±0.5	±1.2	±2.5	±4		Qlight				DWG. NO. QGL/QGLC	
	400~1000	±0.3	±0.8	±2	±4	±10						SCALE 1/1	SHEET 1/1
FOR ANGULAR DIMENSIONS	0~10	±1°	±1°30'	±3°	±1°	±2°						SIZE A4	REV 00
	10~50	±0°30'	±1°	±2°	±1°	±2°						REV 00	SHEET 1/1
	50~120	±0°20'	±0°30'	±1°	±1°	±2°						REV 00	SHEET 1/1
	120~400	±0°10'	±0°13'	±0°30'	±0°30'	±1°						REV 00	SHEET 1/1

A4(297X210)