



MODEL NO		QCML/ QCMLC							
MATERIAL		SIDE COVER-PC							
		LENS-PC							
		HEAT SINK-AL							
		BRACKET-PC							
MODEL		QCML-200/ QCMLC-200	QCML-300/ QCMLC-300	QCML-400/ QCMLC-400	QCML-500/ QCMLC-500	QCML-600/ QCMLC-600	QCML-900/ QCMLC-900	QCML-1200/ QCMLC-1200	QCML-1500/ QCMLC-1500
POWER CONSUMPTION	DC24V	5.5W	6W	11W	11.5W	12W	18W	23W	30W
LED		CHIP LED							
PROTECTION GRADE		WATER & DUST PROOF IP67/IP69K							

MODEL	A	B	C	D
QCML/ QCMLC -200	262	228	45~217	2
QCML/ QCMLC -300	362	328	45~317	2
QCML/ QCMLC -400	462	428	45~417	2
QCML/ QCMLC -500	562	528	45~517	2
QCML/ QCMLC -600	662	628	45~617	2
QCML/ QCMLC -900	962	928	45~917	3
QCML/ QCMLC -1200	1262	1228	45~1217	4
QCML/ QCMLC -1500	1562	1528	45~1517	4

※ D : Recommended quantity of mounting brackets

※POWER CABLE : DC TYPE - UL2464 AWG22(0.3sq X 2C) 450mm

ISO2768-1 : CLASS OF TOLERANCE						SURFACE FINISH	-	-	-	-	1	-
FOR LINEAR DIMENSIONS		f	m	c	Ⓥ		Nr.	DWG. NO.	TITLE/ NAME	MAT'L	QTY	REFERENCE
	0.5~3	±0.05	±0.1	±0.2	-		DSND BY	CHKD BY	CHKD BY	APRV BY	VIEW	DATE
	3~6	±0.05	±0.1	±0.3	±0.5		C.S.GWAK	J.H.PARK		J.K.HAN	3	2021.07.27
	6~30	±0.1	±0.2	±0.5	±1		TITLE			MODEL		
	30~120	±0.15	±0.3	±0.8	±1.5		QCML/QCMLC OUTLINE DRAWING			QCML/QCMLC		
	120~400	±0.2	±0.5	±1.2	±2.5					DWG. NO.		
FOR ANGULAR DIMENSIONS	400~1000	±0.3	±0.8	±2	±4					QCML/QCMLC		
	0~10	±1°		±1°30'	±3°					SCALE		
	10~50	±0°30'		±1°	±2°					SIZE		
	50~120	±0°20'		±0°30'	±1°					REV		
	120~400	±0°10'		±0°13'	±0°30'					SHEET		