



MARK	DATE	REVISION	REVISER	APP .BY
1				
2				
3				

MODEL NO			S60L				
MATERIAL			HOUSING-ABS				
			LENS-AS				
			REFLECTOR-HEAT RESISTING ABS				
COLOR OF LENS			RED(    ), AMBER(    ), GREEN(    ), BLUE(    )				
FLASHES PER MIN.			60 ~ 80				
USE VOLT.	LED	CURRENT	DC12V ~ DC24V		0.08W	MAX.0.120A	
			AC110V			0.025A	
			AC220V			0.015A	
PROTECTION GRADE			WATER & DUST PROOF IP44				
CABLE ENTRY			ø8 LEAD HOLE				
COLOR OF HOUSING			MAKER STANDARD				
ACTION			LED STEADY/FLASHING LIGHT				

ISO2768-1 : CLASS OF TOLERANCE						SURFACE FINISH	-	-	-	-	1	-
FOR LINEAR DIMENSIONS		f	m	Ⓒ	v		Nr.	DWG. NO.	TITLE/ NAME		MAT'L	QT'Y
	0.5~3	±0.05	±0.1	±0.2	-	DSND BY S.H.KIM	CHKD BY J.H.PARK		APRV BY J.K.HAN	VIEW 3	DATE 2019.03.20	
	3~6			±0.3	±0.5							
	6~30	±0.1	±0.2	±0.5	±1							
	30~120	±0.15	±0.3	±0.8	±1.5							
	120~400	±0.2	±0.5	±1.2	±2.5							
400~1000	±0.3	±0.8	±2	±4								
FOR ANGULAR DIMENSIONS	0~10	±1°		±1°30'	±3°				DWG. NO.  S60L_OUT			
	10~50	±0°30'		±1°	±2°				SCALE N/S			
	50~120	±0°20'		±0°30'	±1°				SIZE A4			
	120~400	±0°10'		±0°13'	±0°30'				REV 00			
									SHEET 1/1			

A4(297X210)