



FITTING HOLES
(SCALE 6:1)

※POWER CABLE : DC TYPE - UL2464 AWG22(0.3sq X 2C) 400mm
AC TYPE - VCTFK (0.75sq) x 2C 400mm

MARK	DATE	REVISION	REVISER	APP. BY
①				
②				
③				

MODEL NO		QELTS			
MATERIAL		SIDE COVER : ABS			
		LENS-PC			
		BRACKET-SUS201			
COLOR OF LENS		TRANSLUCENT			
MODEL		QELTS-200	QELTS-300	QELTS-400	QELTS-500
POWER CONSUMPTION	DC24V	3.5W	5W	7W	9W
	AC110V	3W	3.5W	4.5W	5W
	AC220V	3.5W	5W	6.5W	8.5W
LED		CHIP LED			
PROTECTION GRADE		NON WATER-PROOF			

MODEL	A	B	C
QELTS-200	278	200	16~170
QELTS-300	378	300	16~270
QELTS-400	478	400	16~370
QELTS-500	578	500	16~470

ISO2768-1 : CLASS OF TOLERANCE						SURFACE FINISH	-	-	-	-	1	-	
FOR LINEAR DIMENSIONS		f	m	c	Ⓥ		Nr.	DWG. NO.	TITLE/ NAME		MAT'L	QTY	REFERENCE
	0.5~3	±0.05	±0.1	±0.2	-		DSND BY C.S.GWAK	CHKD BY J.H.PARK	CHKD BY 	APRV BY J.K.HAN	VIEW 3	DATE 2021.07.27	
	3~6			±0.3	±0.5								
	6~30	±0.1	±0.2	±0.5	±1								
	30~120	±0.15	±0.3	±0.8	±1.5								
	120~400	±0.2	±0.5	±1.2	±2.5								
400~1000	±0.3	±0.8	±2	±4									
FOR ANGULAR DIMENSIONS	0~10	±1°		±1°30'	±3°					DWG. NO.			
	10~50	±0°30'		±1°	±2°					QELTS			
	50~120	±0°20'		±0°30'	±1°					SCALE 1/1	SIZE A4	REV 00	SHEET 1/1
	120~400	±0°10'		±0°13'	±0°30'								