




※ POWER CABLE : Dura & Flex-F VU(0.5sq X 2C) 450mm

MARK	DATE	REVISION	REVISER	APP .BY
①				
②				
③				

MODEL NO			QMHL-250-D		
MATERIAL			BODY-AL		
			LENS-CHEMICAL TEMPERED GLASS		
			COVER-AL		
			-		
COLOR OF LENS			CLEAR		
USE VOLT.	LED	POWER CONSUMPTION	DC24V	CHIP LED	25W
PROTECTION GRADE			WATER & DUST PROOF IP67 / IP69K		
CABLE ENTRY			M12		

ISO2768-1 : CLASS OF TOLERANCE						SURFACE FINISH	-	-	-	-	1	-
FOR LINEAR DIMENSIONS		f	m	Ⓒ	v		Nr.	DWG. NO.	TITLE/ NAME	MAT'L	QT'Y	REFERENCE
	0.5~3	±0.05	±0.1	±0.2	-		DSND BY	CHKD BY	CHKD BY	APRV BY	VIEW	DATE
	3~6			±0.3	±0.5		S.H.KIM	J.H.PARK		J.K.HAN	3	2019.03.20
	6~30	±0.1	±0.2	±0.5	±1		TITLE			MODEL		
	30~120	±0.15	±0.3	±0.8	±1.5		QMHL-250-D OUTLINE DRAWING			QMHL-250-D		
	120~400	±0.2	±0.5	±1.2	±2.5					DWG. NO.		
400~1000	±0.3	±0.8	±2	±4	QMHL-250-D_OUT							
FOR ANGULAR DIMENSIONS	0~10	±1°		±1°30'	±3°				SCALE	SIZE	REV	SHEET
	10~50	±0°30'		±1°	±2°				N/S	A4	00	1/1
	50~120	±0°20'		±0°30'	±1°							
	120~400	±0°10'		±0°13'	±0°30'							

A4(297X210)