



※ POWER CABLE : Dura & Flex-F VU(0.5sq X 2C) 450mm

MARK	DATE	REVISION	REVISER	APP .BY
①				
②				
③				

MODEL NO		QMHL-150-K		
MATERIAL		BODY-AL		
		LENS-CHEMICAL TEMPERED GLASS		
		COVER-AL		
		BRACKET-SUS430		
COLOR OF LENS		TRANSPARENT		
USE VOLT.	LED	POWER CONSUMPTION	DC24V	CHIP LED 12W
PROTECTION GRADE		WATER & DUST PROOF IP67 / IP69K		
CABLE ENTRY		M12		

ISO2768-1 : CLASS OF TOLERANCE						SURFACE FINISH		-	-	-	-	1	-
FOR LINEAR DIMENSIONS		f	m	(C)	v			Nr.	DWG. NO.	TITLE/ NAME	MAT'L	QTY	REFERENCE
	0.5~3	±0.05	±0.1	±0.2	-			DSND BY	CHKD BY	CHKD BY	APRV BY	VIEW	DATE
	3~6			±0.3	±0.5			S.H.KIM	J.H.PARK		J.K.HAN	3	2019.03.20
	6~30	±0.1	±0.2	±0.5	±1			TITLE QMHL-150-K OUTLINE DRAWING					
	30~120	±0.15	±0.3	±0.8	±1.5			MODEL QMHL-150-K					
	120~400	±0.2	±0.5	±1.2	±2.5			DWG. NO. QMHL-150-K_OUT					
FOR ANGULAR DIMENSIONS	0~10	±1°	±1°30'	±3°				Qlight					
	10~50	±0°30'	±1°	±2°									
	50~120	±0°20'	±0°30'	±1°									
	120~400	±0°10'	±0°13'	±0°30'									
								SCALE	SIZE	REV	SHEET		
								N/S	A4	00	1/1		