



※ POWER CABLE : Dura & Flex-F VU(0.5sq X 2C) 450mm

MARK	DATE	REVISION	REVISER	APP .BY
①				
②				
③				

MODEL NO	QMHL-250-K		
MATERIAL	BODY-AL		
	LENS-CHEMICAL TEMPERED GLASS		
	COVER-AL		
COLOR OF LENS		TRANSPAREN	
USE VOLT.	LED	POWER CONSUMPTION	DC24V
			CHIP LED
			25W
PROTECTION GRADE		WATER & DUST PROOF IP67 / IP69K	
CABLE ENTRY		M12	

ISO2768-1 : CLASS OF TOLERANCE					
FOR LINEAR DIMENSIONS		f	m	(C)	v
	0.5~3	±0.05	±0.1	±0.2	-
	3~6			±0.3	±0.5
	6~30	±0.1	±0.2	±0.5	±1
	30~120	±0.15	±0.3	±0.8	±1.5
	120~400	±0.2	±0.5	±1.2	±2.5
FOR ANGULAR DIMENSION	400~1000	±0.3	±0.8	±2	±4
	0~10	±1°		±1°30'	±3°
	10~50	±0°30'		±1°	±2°
	50~120	±0°20'		±0°30'	±1°
	120~400	±0°10'		±0°13'	±0°30'

SURFACE FINISH		-		1	
Nr.	DWG. NO.	TITLE/ NAME		MAT'L	REFERENCE
DSND BY	CHKD BY	CHKD BY		APRV BY	DATE
S.H.KIM	J.H.PARK			J.K.HAN	2019.03.20
TITLE		QMHL-250-K OUTLINE DRAWING		MODEL	QMHL-250-K
				DWG. NO.	QMHL-250-K_OUT
				SCALE	SIZE
				N/S	A4
				REV	SHEET
				00	1/1

Qlight

A4(297X210)