



MARK	DATE	REVISION	REVISER	APP.BY
△				
△				
△				

MODEL NO		MFL80			
MATERIAL		HOUSING-ABS			
		LENS-PC			
		-			
COLOR OF LENS		RED(), AMBER(), GREEN(), BLUE()			
FLASHES. PER MIN		60 ~ 80			
STROBE FLASHES. PER MIN		70 ~ 80			
REV. PER MIN		120 ~140			
KIND OF FUNCTION		USE VOLT.	FLASHES.	STROBE	REVOLVING
USE VOLT.	CURRNET (MAX.)	DC12V	0.133A	0.110A	0.073A
		DC24V	0.084A	0.074A	0.055A
		AC110V	0.041A	0.035A	0.023A
		AC220V	0.029A	0.025A	0.018A
VOLUME		MAX. 80dB at 1m			
PROTECTION GRADE		WATER & DUST PROOF IP66			
CABLE ENTRY		φ9 LEAD HOLE			
COLOR OF HOUSING		MAKER STANDARD			
ACTION		LED STEADY / FLASHING LIGHT			

ISO2768-1 : CLASS OF TOLERANCE						SURFACE FINISH	-	-	-	-	1	-
FOR LINEAR DIMENSIONS		f	m	Ⓒ	v		Nr.	DWG. NO.	TITLE/ NAME	MAT'L	QTY	REFERENCE
	0.5~3	±0.05	±0.1	±0.2	-	DSND BY S.H.KIM	CHKD BY J.H.PARK	CHKD BY 	APRV BY J.K.HAN	VIEW 3	DATE 2016.08.30	
	3~6			±0.3	±0.5							
	6~30	±0.1	±0.2	±0.5	±1	TITLE MFL80 OUTLINE DRAWING	MODEL MFL80					
	30~120	±0.15	±0.3	±0.8	±1.5			DWG. NO. MFL80_OUT				
	120~400	±0.2	±0.5	±1.2	±2.5				SCALE N/S	SIZE A4	REV 00	SHEET 1/1
400~1000	±0.3	±0.8	±2	±4								
FOR ANGULAR DIMENSIONS	0~10	±1°		±1°30'	±3°							
	10~50	±0°30'		±1°	±2°							
	50~120	±0°20'		±0°30'	±1°							
	120~400	±0°10'		±0°13'	±0°30'							