



FITTING HOLES

MARK	DATE	REVISION	REVISER	APP.BY
①				
②				
③				

MODEL NO		QWCD50			
MATERIAL		HORN-PC			
		HOUSING-PC+ABS			
		-			
COLOR OF LENS		RED(), AMBER(), GREEN(), BLUE()			
USE VOLT.	CURRNET	STANDARD	DC12V ~ 24V	0.2W	MAX. 5.45A
			AC110V ~ 220V		MAX. 0.90A
		SD CARD TYPE	DC12V ~ 24V		MAX. 3.80A
			AC110V ~ 220V		MAX. 0.72A
KIND OF SOUND	VOLUME	WARNING SOUNDS 31Ch			MAX. 115dB at 1m
		MP3 SOUNDS			MAX. 113dB at 1m
PROTECTION GRADE		WATER & DUST PROOF - IP66			
CABLE ENTRY		ø21 CABLE ENTRY			
COLOR OF HOUSING		MAKER STANDARD			
ACTION		LED LAMP STROBE LIGHT			

ISO2768-1 : CLASS OF TOLERANCE						SURFACE FINISH	-												
FOR LINEAR DIMENSIONS			f	m	Ⓒ		v	Nr.	DWG. NO.		TITLE/ NAME		MAT'L		QTY	REFERENCE			
	0.5~3		±0.05	±0.1	±0.2		-	DSND BY		CHKD BY		CHKD BY		APRV BY		VIEW	DATE		
	3~6				±0.3		±0.5	S.H.KIM		J.H.PARK				J.K.HAN		3	2019.03.20		
	6~30		±0.1	±0.2	±0.5		±1												
	30~120		±0.15	±0.3	±0.8		±1.5												
	120~400		±0.2	±0.5	±1.2		±2.5												
400~1000		±0.3	±0.8	±2	±4														
FOR ANGULAR DIMENSIONS	0~10		±1°		±1°30'		±3°												
	10~50		±0°30'		±1°		±2°												
	50~120		±0°20'		±0°30'		±1°												
	120~400		±0°10'		±0°13'		±0°30'												
												DWG. NO.		QWCD50_OUT					
												SCALE		SIZE <td colspan="2">REV<td colspan="2">SHEET</td></td>		REV <td colspan="2">SHEET</td>		SHEET	
												N/S		A4		00		1/1	

