



FITTING HOLES

MARK	DATE	REVISION	REVISER	APP.BY
1				
2				
3				

MODEL NO		QWCD35			
MATERIAL		HORN-PC			
		HOUSING-PC+ABS			
		-			
COLOR OF LENS		RED(), AMBER(), GREEN(), BLUE()			
USE VOLT.	CURRNET	STANDARD	DC12V ~ 24V	0.2W	MAX. 1.30A
			AC110V ~ 220V		MAX. 0.35A
		SD CARD TYPE	DC12V ~ 24V		MAX. 1.20A
			AC110V ~ 220V		MAX. 0.31A
KIND OF SOUND	VOLUME	WARNING SOUNDS 31Ch			MAX. 115dB at 1m
		MP3 SOUNDS			MAX. 113dB at 1m
PROTECTION GRADE		WATER & DUST PROOF - IP66			
CABLE ENTRY		ø21 CABLE ENTRY			
COLOR OF HOUSING		MAKER STANDARD			
ACTION		LED LAMP STROBE LIGHT			

ISO2768-1 : CLASS OF TOLERANCE						SURFACE FINISH	-										
FOR LINEAR DIMENSIONS		f	m	Ⓒ	v		Nr.	DWG. NO.			TITLE/ NAME			MAT'L	QT'Y	REFERENCE	
	0.5~3	±0.05	±0.1	±0.2	-	DSND BY S.H.KIM	CHKD BY J.H.PARK	CHKD BY 	APRV BY J.K.HAN	VIEW 3	DATE 2019.03.20						
	3~6			±0.3	±0.5												
	6~30	±0.1	±0.2	±0.5	±1												
	30~120	±0.15	±0.3	±0.8	±1.5												
	120~400	±0.2	±0.5	±1.2	±2.5												
400~1000	±0.3	±0.8	±2	±4													
FOR ANGULAR DIMENSIONS	0~10	±1°		±1°30'	±3°	<div></div>											
	10~50	±0°30'		±1°	±2°												
	50~120	±0°20'		±0°30'	±1°												
	120~400	±0°10'		±0°13'	±0°30'												
						TITLE			QWCD35 OUTLINE DRAWING			MODEL			QWCD35		
												DWG. NO.			QWCD35_OUT		
												SCALE	SIZE	REV	SHEET		
												N/S	A4	00	1/1		

Qlight

A4(297X210)