



MARK	DATE	REVISION	REVISER	APP .BY
①				
②				
③				

MODEL NO				QWTL / QWTL-BZ / QWTLF / QWTLF-BZ			
MATERIAL				HOUSING-ABS			
				LENS-AS			
				COVER-ABS			
COLOR OF LENS				RED(), AMBER(), GREEN(), BLUE(), WHITE()			
USE VOLT.	LED	CURRENT	DC12V	0.2W	MAX. 0.065A		
			DC24V		MAX. 0.050A		
			AC110V		MAX. 0.025A		
			AC220V		MAX. 0.025A		
VOLUME			MAX. 85dB at 1m				
PROTECTION GRADE			WATER & DUST PROOF IP54				
CABLE ENTRY			ø13 LEAD HOLE				
COLOR OF HOUSING			MAKER STANDARD				
ACTION			LED STEADY / FLASHING LIGHT				

LAYER	L
1	121
2	162
3	203
4	244
5	285

ISO2768-1 : CLASS OF TOLERANCE						SURFACE FINISH	-	-	-	-	1	-	
FOR LINEAR DIMENSIONS		f	m	Ⓒ	v		Nr.	DWG. NO.	TITLE/NAME	MAT'L	QTY	REFERENCE	
	0.5~3	±0.05	±0.1	±0.2	-	DSND BY S.H.KIM	CHKD BY J.H.PARK		APRV BY J.K.HAN	VIEW 3	DATE 2016.08.30		
	3~6			±0.3	±0.5								
	6~30	±0.1	±0.2	±0.5	±1	TITLE QWT OUTLINE DRAWING 						MODEL QWT DWG. NO. QWT_OUT SCALE N/S SIZE A4 REV 00 SHEET 1/1	
	30~120	±0.15	±0.3	±0.8	±1.5								
	120~400	±0.2	±0.5	±1.2	±2.5								
	400~1000	±0.3	±0.8	±2	±4								
FOR ANGULAR DIMENSIONS	0~10	±1°		±1°30'	±3°								
	10~50	±0°30'		±1°	±2°								
	50~120	±0°20'		±0°30'	±1°								
	120~400	±0°10'		±0°13'	±0°30'								

A4(297X210)