



FITTING HOLES

MARK	DATE	REVISION	REVISER	APP .BY
1				
2				
3				

MODEL NO		QA70HLS			
MATERIAL		LENS-PC			
		HOUSING-ABS+GF			
		-			
COLOR OF LENS		RED(), AMBER()			
FLASHES PER MIN.		45 ~ 55			
USE VOLT.	LED	CURRENT	DC12V ~ 24V	0.5W	MAX. 0.650A
PROTECTION GRADE		WATER & DUST PROOF IP66			
CABLE ENTRY		ø9 LEAD HOLE			
COLOR OF HOUSING		MAKER STANDARD			
ACTION		LED LAMP STROBE LIGHT			

ISO2768-1 : CLASS OF TOLERANCE						SURFACE FINISH							
FOR LINEAR DIMENSIONS		f	m	Ⓒ	v		Nr.	DWG. NO.	TITLE/ NAME	MAT'L	QT'Y	REFERENCE	
	0.5~3	±0.05	±0.1	±0.2	-	DSND BY S.H.KIM	CHKD BY J.H.PARK	CHKD BY 	APRV BY J.K.HAN	VIEW 3	DATE 2019.03.20		
	3~6			±0.3	±0.5								
	6~30	±0.1	±0.2	±0.5	±1								
	30~120	±0.15	±0.3	±0.8	±1.5								
	120~400	±0.2	±0.5	±1.2	±2.5								
400~1000	±0.3	±0.8	±2	±4									
FOR ANGULAR DIMENSIONS	0~10	±1°		±1°30'	±3°								
	10~50	±0°30'		±1°	±2°								
	50~120	±0°20'		±0°30'	±1°								
	120~400	±0°10'		±0°13'	±0°30'								
									DWG. NO.		QA70HLS_OUT		
									SCALE N/S	SIZE A4	REV 00	SHEET 1/1	