




MARK	DATE	REVISION	REVISER	APP.BY
1				
2				
3				

MODEL NO			S180R			
MATERIAL			HOUSING-SUS			
			LENS-AS			
			REFLECTOR-PC			
COLOR OF LENS			RED(), AMBER(), GREEN(), BLUE()			
REV. PER MIN.			120 ~ 140			
USE VOLT.	BLUB	CURRENT	DC12V	35W	MAX. 3.077A	
			DC24V		MAX. 1.544A	
			AC110V		MAX. 0.388A	
			AC220V		MAX. 0.194A	
PROTECTION GRADE			WATER & DUST PROOF IP44			
CABLE ENTRY			φ10 LEAD HOLE			
COLOR OF HOUSING			MAKER STANDARD			
ACTION			BULB REVOLVING WARNING LIGHT			

ISO2768-1 : CLASS OF TOLERANCE						SURFACE FINISH	-	-	-	-	1	-
FOR LINEAR DIMENSIONS		f	m	Ⓒ	v		Nr.	DWG. NO.	TITLE/ NAME	MAT'L	QTY	REFERENCE
	0.5~3	±0.05	±0.1	±0.2	-		DSND BY S.H.KIM	CHKD BY J.H.PARK	CHKD BY 	APRV BY J.K.HAN	VIEW 3	DATE 2016.08.30
	3~6			±0.3	±0.5							
	6~30	±0.1	±0.2	±0.5	±1		TITLE			MODEL		
	30~120	±0.15	±0.3	±0.8	±1.5		S180R OUTLINE DRAWING			S180R		
	120~400	±0.2	±0.5	±1.2	±2.5				DWG. NO.			
400~1000	±0.3	±0.8	±2	±4	S180R_OUT							
FOR ANGULAR DIMENSIONS	0~10	±1°		±1°30'	±3°				SCALE	SIZE	REV	SHEET
	10~50	±0°30'		±1°	±2°				N/S	A4	00	1/1
	50~120	±0°20'		±0°30'	±1°							
	120~400	±0°10'		±0°13'	±0°30'							