



ISO2768-1 : CLASS OF TOLERANCE					
FOR LINEAR DIMENSIONS	0.5~3	±0.05	±0.1	±0.2	-
	3~6	±0.05	±0.1	±0.3	±0.5
	6~30	±0.1	±0.2	±0.5	±1
	30~120	±0.15	±0.3	±0.8	±1.5
	120~400	±0.2	±0.5	±1.2	±2.5
	400~1000	±0.3	±0.8	±2	±4
FOR ANGULAR DIMENSIONS	0~10	±1°	±1°30'	±3°	
	10~50	±0°30'	±1°	±2°	
	50~120	±0°20'	±0°30'	±1°	
	120~400	±0°10'	±0°13'	±0°30'	

SURFACE FINISH

Nr.	DWG. NO.	TITLE/ NAME	MAT'L	QTY	REFERENCE
DSND BY	CHKD BY	CHKD BY	APRV BY	VIEW	DATE
Y.C.KO	J.H.PARK		J.K.HAN	3	2020. 10. 26.
TITLE			MODEL		
SKTLB OUTLINE DRAWING			SKTLB		
Qlight			DWG. NO.		
			SKTLB_OUT		
SCALE	SIZE	REV	SHEET		
N/S	A4	00	1/1		

MARK	DATE	REVISION	REVISER	APP. BY
1				
2				
3				

MODEL NO			SKTLB			
MATERIAL			HOUSING-PC			
			LENS-PC			
			-			
COLOR OF LENS			RED(), AMBER(), GREEN(), BLUE(), WHITE()			
FLASHES. PER MIN			60 ~ 80			
USE VOLT.	LED	CURRNET	DC12V	3W	MAX.1.250V	
			DC24V		MAX.0.705V	
VOLUME			MAX. 105 at 1m			
PROTECTION GRADE			WATER & DUST PROOF IP66			
CABLE ENTRY			ø9 LEAD HOLE			
COLOR OF HOUSING			MAKER STANDARD			
ACTION			LED STEADY / FLASHING LIGHT			