



MARK	DATE	REVISION	REVISER	APP.BY
1				
2				
3				

MODEL NO			ST56MEL-BZ-2-24-RG-TR		
MATERIAL			HOUSING-ABS		
			LENS-AS		
			-		
COLOR OF LENS			RED(), GREEN()		
FLASHING PER MIN.			60 ~ 80		
USE VOLT.	LED	CURRENT	DC24V	0.08W	MAX. 0.110A
VOLUME			MAX. 90 dB at 1m		
PROTECTION GRADE			WATER & DUST PROOF IP23		
CABLE ENTRY			ø8 LEAD HOLE		
COLOR OF HOUSING			MAKER STANDARD		
ACTION			LED STEADY/ FLASHING SIGNAL TOWER LAMP		

ISO2768-1 : CLASS OF TOLERANCE						SURFACE FINISH	-	-	-	-	1	-
FOR LINEAR DIMENSIONS		f	m	Ⓒ	v		Nr.	DWG. NO.	TITLE/ NAME	MAT'L	QTY	REFERENCE
	0.5~3	±0.05	±0.1	±0.2	-	DSND BY S.H.KIM	CHKD BY J.H.PARK	CHKD BY 	APRV BY J.K.HAN	VIEW 3	DATE 2018.01.12	
	3~6			±0.3	±0.5							
	6~30	±0.1	±0.2	±0.5	±1	TITLE ST56MEL OUTLINE DRAWING 	MODEL ST56MEL-BZ-2-24-RG-TR DWG. NO. ST56MEL_OUT					
	30~120	±0.15	±0.3	±0.8	±1.5			SCALE N/S	SIZE A4	REV 00	SHEET 1/1	
	120~400	±0.2	±0.5	±1.2	±2.5							
400~1000	±0.3	±0.8	±2	±4								
FOR ANGULAR DIMENSIONS	0~10	±1°		±1°30'	±3°							
	10~50	±0°30'		±1°	±2°							
	50~120	±0°20'		±0°30'	±1°							
	120~400	±0°10'		±0°13'	±0°30'							