




MARK	DATE	REVISION	REVISER	APP.BY
①				
②				
③				

MODEL NO		SMCL80-BZ-2-24-RG-TR		
MATERIAL		HOUSING-ABS		
		LENS-AS		
		REFLECTOR-HEAT RESISTING ABS		
COLOR OF LENS		RED(), GREEN()		
FLASHING PER MIN.		60 ~ 80		
USE VOLT.	LED	CURRENT	DC24V	0.08W
				MAX. 0.063A
VOLUME		MAX. 90 dB at 1m		
PROTECTION GRADE		WATER & DUST PROOF IP44		
CABLE ENTRY		ø10 LEAD HOLE		
COLOR OF HOUSING		MAKER STANDARD		
ACTION		MULTIPLE COLORS LED SIGNAL STEADY/ FLASHING LIGHT		

ISO2768-1 : CLASS OF TOLERANCE						SURFACE FINISH	-	-	-	-	1	-
FOR LINEAR DIMENSIONS		f	m	Ⓒ	v		Nr.	DWG. NO.	TITLE/ NAME	MAT'L	QT'Y	REFERENCE
	0.5~3	±0.05	±0.1	±0.2	-	DSND BY	CHKD BY	CHKD BY	APRV BY	VIEW	DATE	
	3~6			±0.3	±0.5	S.H.KIM	J.H.PARK		J.K.HAN	3	2018.01.12	
	6~30	±0.1	±0.2	±0.5	±1	TITLE			MODEL			
	30~120	±0.15	±0.3	±0.8	±1.5	SMCL80 OUTLINE DRAWING			SMCL80-BZ-2-24-RG-TR			
	120~400	±0.2	±0.5	±1.2	±2.5				DWG. NO.			
400~1000	±0.3	±0.8	±2	±4	SMCL80_OUT							
FOR ANGULAR DIMENSIONS	0~10	±1°		±1°30'	±3°			SCALE	SIZE	REV	SHEET	
	10~50	±0°30'		±1°	±2°			N/S	A4	00	1/1	
	50~120	±0°20'		±0°30'	±1°							
	120~400	±0°10'		±0°13'	±0°30'							