




MARK	DATE	REVISION	REVISER	APP .BY
△				
△				
△				

MODEL NO	QMFLN				
MATERIAL	BODY-AL				
	LENS-TEMPERED GLASS				
	SIDE COVER-AL				
	BRACKET-SPC-1				
COLOR OF LENS	CLEAR				
MODEL	QMFLN-200	QMFLN-300	QMFLN-400	QMFLN-500	QMFLN-600
POWER CONSUMPTION	DC 24V	5.6W	12.5W	20W	25W
LED	CHIP LED				
PROTECTION GRADE	WATER & DUST PROOF IP67				
CABLE ENTRY	M12				



※전원선 규격 : Dura & Flex-FVU(0.5sq) x 2C 450mm

MODEL	L1	PCD	L2
QMFLN-200	190	210	230
QMFLN-300	290	310	330
QMFLN-400	400	420	440
QMFLN-500	500	520	540
QMFLN-600	600	620	640

ISO2768-1 : CLASS OF TOLERANCE						SURFACE FINISH	-		QMFLN SERIES		-	-	-
FOR LINEAR DIMENSIONS		f	Ⓜ	c	v		Nr.	DWG NO.	TITLE/NAME		MAL'T	QT'Y	REFERENCE
	0.5~3	±0.05	±0.1	±0.2	-	DSND BY	CHKD BY	CHKD BY	APRV BY	VIEW	DATE		
	3~6			±0.3	±0.5	K.H.PARK	J.H.PARK	J.I.BAE	J.K.HAN	3	2022. 2. 24.		
	6~30	±0.1	±0.2	±0.5	±1	TITLE			MODEL				
	30~120	±0.15	±0.3	±0.8	±1.5	QMFLN-OUTLINE DRAWING			QMFLN SERIES				
	120~400	±0.2	±0.5	±1.2	±2.5								
400~1000	±0.3	±0.8	±2	±4	DWG. NO.								QMFLN-SERIES
FOR ANGULAR DIMENSIONS	0~10	±1°		±1°30'	±3°	SCALE		SIZE	REV	SHEET			
	10~50	±0°30'		±1°	±2°	N/S		A4	00	1/1			
	50~120	±0°20'		±0°30'	±1°								
	120~400	±0°10'		±0°13'	±0°30'								

6 A4(297X210)