



FITTING HOLES

MARK	DATE	REVISION	REVISER	APP.BY
1				
2				
3				

MODEL NO		QWCD35T			
MATERIAL		HORN-PC			
		HOUSING-PC+ABS			
		-			
COLOR OF LENS		RED(), AMBER(), GREEN(), BLUE()			
USE VOLT.	CURRENT	STANDARD	DC12V ~ 24V	0.2W	MAX. 1.300A
			AC110V ~ 220V		MAX. 0.350A
		SD CARD TYPE	DC12V ~ 24V		MAX. 1.200A
			AC110V ~ 220V		MAX. 0.310A
CHANNEL		BIT INPUT		5CH(ONLY SD-CARD)	
		BINARY INPUT		31CH	
KIND OF SOUND	VOLUME	WARNING SOUNDS 31Ch		MAX. 115dB at 1m	
		MP3 SOUNDS		MAX. 113dB at 1m	
PROTECTION GRADE		WATER & DUST PROOF - IP66			
CABLE ENTRY		CABLE GLAND "PG13.5" x 2			
COLOR OF HOUSING		MAKER STANDARD			
ACTION		LED LAMP STROBE LIGHT			

ISO2768-1 : CLASS OF TOLERANCE						-						
FOR LINEAR DIMENSIONS		f	m	Ⓒ	v	Nr.	DWG. NO.	TITLE/ NAME		MAT'L	QTY	REFERENCE
	0.5~3	±0.05	±0.1	±0.2	-	DSND BY C.S.GWAK	CHKD BY J.H.PARK	CHKD BY 	APRV BY J.K.HAN	VIEW 3	DATE 2021.10.08	
	3~6			±0.3	±0.5							
	6~30	±0.1	±0.2	±0.5	±1							
	30~120	±0.15	±0.3	±0.8	±1.5							
	120~400	±0.2	±0.5	±1.2	±2.5							
400~1000	±0.3	±0.8	±2	±4								
						TITLE QWCD35T OUTLINE DRAWING			MODEL QWCD35T			
FOR ANGULAR DIMENSIONS									DWG. NO. QWCD35T_OUT			
									SCALE 1/1	SIZE A4	REV 01	SHEET 1/1

A4(297X210)