QTR70(M)L-USB

IP54 | +50°C -30°C | BUZZER | 85dB | RoHS

QTR70(M)L-USB Series

QTR70(M)L-USB Ø70mm USB Tower Light, Pole mount

Model number		Layers	Certificates	Color
QTR70(M)L-USB-BZ QTRA70(M)L-USB-BZ	5 Buzzer sounds	1 layer 2 layers 3 layers 4 layers 5 layers	CE	1 layer: R 2 layers: R G 3 layers: R A G 4 layers: R A G B 5 layers: R A G B W

Technical Diagram

Units : mm

·QTR70L-USB-BZ



LAYER	L1	L2
1	357	199
2	407	249
3	457	299
4	507	349
5	557	399



·QTR70ML-USB-BZ



Wiring Instructions

· Connect both USB connector and USB power connector to PC

Mounting bracket

Standard	LB24	LW24	QZ24	SZ24	QL24	SL24
Steel	Steel	ABS	ABS	Al	ABS	Al

※ Please refer to [Tower Light Mounting bracket] on this catalogue for detailed dimensions

Customization

· Customized color arrangement available
· Customized pole length available
· Wall mount bracket

Wall mount bracket TWS80

Wall mount bracket TWA80

Ordering Specifications

QTR70L-USB-BZ	-	3	-	RAG	-	LW24
[Model number]		[Layers]		[Color]		[Bracket]
QTR70L-USB-BZ QTR70ML-USB-BZ QTRA70L-USB-BZ QTRA70ML-USB-BZ		1-1 Layers 2-2 Layers 3-3 Layers 4-4 Layers 5-5 Layers		R-Red A-Amber G-Green B-Blue W-White		None-Standard Bracket -LB24 -LW24 -QZ24 -SZ24 -QL24 -SL24

※ Mount brackets are available for the pole mount type(QTR70L-USB Series) only