



MARK	DATE	REVISION	REVISER	APP .BY
△				
△				
△				

MODEL NO	QTG(A)70(M)L-ETN	
MATERIAL	HOUSING-ABS	
	LENS-PC	
	PIPE-AL	
COLOR OF LENS	RED(), AMBER(), GREEN(), BLUE(), WHITE()	
SOUND	BZ	5 Buzzer sounds
VOLUME	MAX. 90dB at 1m	
PROTECTION GRADE	WATER & DUST PROOF IP65 (BZ TYPE-IP54)	
CABLE ENTRY	14 LEAD HOLE	
COLOR OF HOUSING	MAKER STANDARD	
ACTION	LED STEADY / FLASHING LIGHT	

LAYER	L1	L2
1	357	199
2	407	249
3	457	299
4	507	349
5	557	399

ISO2768-1 : CLASS OF TOLERANCE					
FOR LINEAR DIMENSIONS		f	m	Ⓢ	v
	0.5~3			±0.2	-
	3~6	±0.05	±0.1	±0.3	±0.5
	6~30	±0.1	±0.2	±0.5	±1
	30~120	±0.15	±0.3	±0.8	±1.5
	120~400	±0.2	±0.5	±1.2	±2.5
FOR ANGULAR DIMENSIONS	400~1000	±0.3	±0.8	±2	±4
	0~10	±1°		±1°30'	±3°
	10~50	±0°30'		±1°	±2°
	50~120	±0°20'		±0°30'	±1°
	120~400	±0°10'		±0°13'	±0°30'

SURFACE FINISH

-	-	-	-	1	-
Nr.	DWG. NO.	TITLE/ NAME		MAT'L	REFERENCE
DSND BY	CHKD BY	CHKD BY	APRV BY	VIEW	DATE
J.H.PARK	J.H.PARK		J.K.HAN	3	2019.07.10
TITLE			MODEL		
QTG70(M)L-ETN OUTLINE DRAWING			QTG70(M)L-ETN		
			DWG. NO. QTG70(M)L-ETN_OUT		
			SCALE N/S	SIZE A4	REV 00
				SHEET 1/1	

A4(297X210)