



MARK	DATE	REVISION	REVISER	APP.BY
①				
②				
③				

MODEL NO			SK/SKH				
MATERIAL			HOUSING-PC				
			LENS-PC				
			REFLECTOR-PC/ SUS				
COLOR OF LENS			RED(), AMBER(), GREEN(), BLUE()				
REV. PER MIN.			120 ~ 140				
USE VOLT.	BULB	CURRENT	SK	DC12V	15W	MAX. 1.544A	
				DC24V		MAX. 0.766A	
	SKH	DC12V	35W	MAX. 3.077A			
		DC24V		MAX. 1.544A			
PROTECTION GRADE			WATER & DUST PROOF IP54				
CABLE ENTRY			ø10 LEAD HOLE				
COLOR OF HOUSING			MAKER STANDARD				
ACTION			BULB REVOLVING WARNING LIGHT				

ISO2768-1 : CLASS OF TOLERANCE						SURFACE FINISH	-	-	-	-	1	-
FOR LINEAR DIMENSIONS		f	m	Ⓒ	v		Nr.	DWG. NO.	TITLE/ NAME	MAT'L	QTY	REFERENCE
	0.5~3	±0.05	±0.1	±0.2	-		DSND BY S.H.KIM	CHKD BY J.H.PARK	CHKD BY 	APRV BY J.K.HAN	VIEW 3	DATE 2016.08.30
	3~6			±0.3	±0.5							
	6~30	±0.1	±0.2	±0.5	±1		TITLE			MODEL		
	30~120	±0.15	±0.3	±0.8	±1.5		SK/SKH OUTLINE DRAWING			SK/SKH		
	120~400	±0.2	±0.5	±1.2	±2.5				DWG. NO.			
400~1000	±0.3	±0.8	±2	±4	SK/SKH_OUT							
FOR ANGULAR DIMENSIONS	0~10	±1°		±1°30'	±3°				SCALE			
	10~50	±0°30'		±1°	±2°				SIZE			
	50~120	±0°20'		±0°30'	±1°				REV			
	120~400	±0°10'		±0°13'	±0°30'				SHEET			
									N/S	A4	00	1/1