



※ *(167) represents size without protection cage.

MARK	DATE	REVISION	REVISER	APP.BY
1				
2				
3				

MODEL NO			SH1L				
MATERIAL			HOUSING-AL				
			LENS-PC				
			REFLECTOR-HEAT RESISTANT ABS				
			PROTECTION CAGE-SUS316L				
COLOR OF LENS			RED(), AMBER(), GREEN(), BLUE()				
FLASHING PER MIN.			60 ~ 80				
USE VOLT.	LED	CURRENT	DC12V		0.08W	MAX. 0.300A	
			DC24V			MAX. 0.200A	
			AC110V			MAX. 0.080A	
			AC220V			MAX. 0.040A	
PROTECTION GRADE			WATER & DUST PROOF IP66				
CABLE ENTRY			1/2" PF				
COLOR OF HOUSING			MUNSELL NO. 7.5BG 7/2				
ACTION			LED STEADY/ FLASHING LIGHT				

ISO2768-1 : CLASS OF TOLERANCE						SURFACE FINISH							
FOR LINEAR DIMENSIONS		f	m	(C)	v			Nr.	DWG. NO.	TITLE/ NAME		MAT'L	1
	0.5~3	±0.05	±0.1	±0.2	-			DSND BY	CHKD BY	TITLE/ NAME		APRV BY	QTY
	3~6	±0.1	±0.2	±0.3	±0.5			S.H.KIM	J.H.PARK	CHKD BY		J.K.HAN	VIEW
	6~30	±0.1	±0.2	±0.5	±1							DATE	REFERENCE
	30~120	±0.15	±0.3	±0.8	±1.5							3	2016.08.30
	120~400	±0.2	±0.5	±1.2	±2.5								
FOR ANGULAR DIMENSIONS	0~10	±1°	±1°30'	±2°	±4°			TITLE		SH1L		MODEL	
	10~50	±0°30'	±1°	±2°				SH1L OUTLINE DRAWING				SH1L	
	50~120	±0°20'	±0°30'	±1°								SH1L_OUT	
	120~400	±0°10'	±0°13'	±0°30'								SCALE	SHEET
												N/S	1/1
												SIZE	REV
												A4	00

Qlight

A4(297X210)