



※ *(167) represents size without protection cage.

MARK	DATE	REVISION	REVISER	APP.BY
①				
②				
③				

MODEL NO			SH1T			
MATERIAL			HOUSING-AL			
			LENS-PC			
			REFLECTOR-PC			
			PROTECTION CAGE-SUS316L			
COLOR OF LENS			RED(), AMBER(), GREEN(), BLUE()			
REV. PER MIN.			120 ~ 140			
USE VOLT.	BULB	CURRENT	DC12V	15W	MAX. 1.544A	
			DC24V		MAX. 0.766A	
			AC110V		MAX. 0.204A	
			AC220V		MAX. 0.102A	
PROTECTION GRADE			WATER & DUST PROOF IP66			
CABLE ENTRY			1/2" PF			
COLOR OF HOUSING			MUNSELL NO. 7.5BG 7/2			
ACTION			BULB REVOLVING WARNING LIGHT			

ISO2768-1 : CLASS OF TOLERANCE						SURFACE FINISH	-	-	-	-	1	-
FOR LINEAR DIMENSIONS		f	m	Ⓒ	v		Nr.	DWG. NO.	TITLE/ NAME	MAT'L	QTY	REFERENCE
	0.5~3	±0.05	±0.1	±0.2	-	DSND BY S.H.KIM	CHKD BY J.H.PARK	CHKD BY 	APRV BY J.K.HAN	VIEW 3	DATE 2016.08.30	
	3~6			±0.3	±0.5							
	6~30	±0.1	±0.2	±0.5	±1	TITLE SH1T OUTLINE DRAWING 						
	30~120	±0.15	±0.3	±0.8	±1.5							
	120~400	±0.2	±0.5	±1.2	±2.5							
400~1000	±0.3	±0.8	±2	±4	MODEL SH1T							
FOR ANGULAR DIMENSIONS	0~10	±1°		±1°30'	±3°	DWG. NO. SH1T_OUT						
	10~50	±0°30'		±1°	±2°	SCALE N/S						
	50~120	±0°20'		±0°30'	±1°							
	120~400	±0°10'		±0°13'	±0°30'							SIZE A4

Qlight

A4(297X210)