



※ *(167) represents size without protection cage.

ISO2768-1 : CLASS OF TOLERANCE						SURFACE FINISH	-	-	-	-	1	-
FOR LINEAR DIMENSIONS		f	m	Ⓒ	v		Nr.	DWG. NO.	TITLE/ NAME		MAT'L	QTY
	0.5~3	±0.05	±0.1	±0.2	-	DSND BY S.H.KIM	CHKD BY J.H.PARK	CHKD BY 	APRV BY J.K.HAN	VIEW 3	DATE 2016.08.30	
	3~6			±0.3	±0.5							
	6~30	±0.1	±0.2	±0.5	±1							
	30~120	±0.15	±0.3	±0.8	±1.5							
	120~400	±0.2	±0.5	±1.2	±2.5							
400~1000	±0.3	±0.8	±2	±4								
FOR ANGULAR DIMENSIONS	0~10	±1°		±1°30'	±3°					DWG. NO. SH1TL_OUT		
	10~50	±0°30'		±1°	±2°							
	50~120	±0°20'		±0°30'	±1°							
	120~400	±0°10'		±0°13'	±0°30'							
										SCALE N/S	SIZE A4	REV 00

MARK	DATE	REVISION	REVISER	APP .BY
①				
②				
③				

MODEL NO			SH1TL			
MATERIAL			HOUSING-AL			
			LENS-PC			
			REFLECTOR-HEAT RESISTANT ABS			
			PROTECTION CAGE-SUS316L			
COLOR OF LENS			RED(), AMBER(), GREEN(), BLUE()			
FLASHING PER MIN.			60 ~ 80			
USE VOLT.	LED	CURRENT	DC12V	0.08W	MAX. 0.300A	
			DC24V		MAX. 0.200A	
			AC110V		MAX. 0.060A	
			AC220V		MAX. 0.030A	
PROTECTION GRADE			WATER & DUST PROOF IP66			
CABLE ENTRY			1/2" PF			
COLOR OF HOUSING			MUNSELL NO. 7.5BG 7/2			
ACTION			LED STEADY/FLASHING LIGHT			