




LAYER	L
1	162
2	256
3	350



MARK	DATE	REVISION	REVISER	APP .BY
1				
2				
3				

MODEL NO			SR			
MATERIAL			HOUSING-ABS			
			LENS-AS			
			REFLECTOR-HEAT RESISTING ABS			
COLOR OF LENS			RED(), AMBER(), GREEN()			
REV. PER MIN			120 ~ 140			
USE VOLT.	BULB	CURRENT	DC12V	5W	MAX. 0.488A	LAYER1
			DC24V		MAX. 0.310A	LAYER1
			AC110V		MAX. 0.102A	LAYER1
			AC220V		MAX. 0.051A	LAYER1
PROTECTION GRADE			WATER & DUST PROOF IP44			
CABLE ENTRY			ø13 LEAD HOLE			
COLOR OF HOUSING			MAKER STANDARD			
ACTION			BULB REVOLVING WARNING LIGHT			

ISO2768-1 : CLASS OF TOLERANCE						SURFACE FINISH	-	-	-	-	1	-
FOR LINEAR DIMENSIONS		f	m	Ⓒ	v		Nr.	DWG. NO.	TITLE/ NAME	MAT'L	QTY	REFERENCE
	0.5~3	±0.05	±0.1	±0.2	-		DSND BY S.H.KIM	CHKD BY J.H.PARK	CHKD BY 	APRV BY J.K.HAN	VIEW 3	DATE 2016.08.30
	3~6			±0.3	±0.5							
	6~30	±0.1	±0.2	±0.5	±1							
	30~120	±0.15	±0.3	±0.8	±1.5							
	120~400	±0.2	±0.5	±1.2	±2.5							
400~1000	±0.3	±0.8	±2	±4								
FOR ANGULAR DIMENSIONS	0~10	±1°		±1°30'	±3°	<div>TITLE</div> <div>SR</div> <div>OUTLINE DRAWING</div> <div></div> <div>MODEL</div> <div>SR</div>						
	10~50	±0°30'		±1°	±2°							
	50~120	±0°20'		±0°30'	±1°							
	120~400	±0°10'		±0°13'	±0°30'							
						DWG. NO.			SR_OUT			
						SCALE N/S	SIZE A4	REV 00	SHEET 1/1			

Qlight

A4(297X210)