



※ *(167) represents size without protection cage.

MARK	DATE	REVISION	REVISER	APP.BY
1				
2				
3				

MODEL NO			SH1TS			
MATERIAL			HOUSING-AL			
			LENS-PC			
			PROTECTION CAGE-SUS316L			
COLOR OF LENS			RED(), AMBER(), GREEN(), BLUE()			
FLASHING PER MIN.			60 ~ 80			
USE VOLT.	XENON	CURRENT	DC12V	6W	MAX. 1.001A	
			DC24V		MAX. 0.616A	
			AC110V		MAX. 0.133A	
			AC220V		MAX. 0.106A	
PROTECTION GRADE			WATER & DUST PROOF IP66			
CABLE ENTRY			1/2" PF			
COLOR OF HOUSING			MUNSELL NO. 7.5BG 7/2			
ACTION			XENON LAMP STROBE LIGHT			

ISO2768-1 : CLASS OF TOLERANCE						SURFACE FINISH	-	-	-	-	1	-					
FOR LINEAR DIMENSIONS		f	m	Ⓒ	v		Nr.	DWG. NO.	TITLE/ NAME	MAT'L	QTY	REFERENCE					
	0.5~3	±0.05	±0.1	±0.2	-	DSND BY S.H.KIM	CHKD BY J.H.PARK	CHKD BY 	APRV BY J.K.HAN	VIEW 3	DATE 2016.08.30						
	3~6			±0.3	±0.5												
	6~30	±0.1	±0.2	±0.5	±1	TITLE SH1TS OUTLINE DRAWING											
	30~120	±0.15	±0.3	±0.8	±1.5							MODEL SH1TS					
	120~400	±0.2	±0.5	±1.2	±2.5												
400~1000	±0.3	±0.8	±2	±4	DWG. NO. SH1TS_OUT												
FOR ANGULAR DIMENSIONS	0~10	±1°		±1°30'							±3°						
	10~50	±0°30'		±1°							±2°						
	50~120	±0°20'		±0°30'							±1°						
	120~400	±0°10'		±0°13'							±0°30'						
						SCALE N/S		SIZE A4	REV 00	SHEET 1/1							

A4(297X210)